



e food information supplied by Thomas Ridley Foodservice has been provided the respective product manufacturer. Whilst we use reasonable endeavours to each this information and ensure its accuracy, we do not give any warrantly hether express or implied), guarantee or representation that it is true, accurate complete in any respect.

As product information, ingredients, nutritional guides and dietary or allergy advice may change from time to time, we recommend that you always carefully read the product label prior to using or consuming any such products. You should not sidely rely upon the information we provide and make your own assessment as to the suitability or otherwise of any given product.

W&H Marriage and Sons Ltd, Chelmer Mills, New Street, Chelmsford Essex CM1 1PN Lessessment as to Telephone: 01245 354455, Fax: 01245 261492, Email: floursales@marriagesmillers.co.uk, Web: www.flour.co.uk

Product Technical Specification

1.	Product

Very Strong 100% Canadian White Bread Flour

2. Product Code

Bag Size

60008D

3.

B
BREAD
VERY HIGH P FOR BREAD, R & PASTA



4. Description

Made from 100% Canadian wheat, a very high protein for bread, rolls and pasta. Suitable for bread machines

5. Milling Process

Roller Milled

6. Extraction Rate (Average)

75%

7. Ingredients (Declared)

Flour (wheat flour, calcium, iron, niacin, thiamin)

8. Undeclared Processing Aid

Fungal Alpha Amylase, Xylanase

9. Analytical Parameters				
	Method	Unit	Target	Range
Protein (N x 5.7)	NIR	%	12.5	12.2 +
Moisture	NIR	%	14.0	13.1 - 15.0
Colour Grade	Kent Jones	KJ	1.0	<1.5
Fallling Number	Hagberg	sec	250+	>250
Water Absorption	Farinograph	%	61	Not Routinely Tested

10.	Physical Standards and Characteristics		
A free	A free flowing white powder free from odours		

Date Issued 04/07/23 Iss	ssued By	C Bunn





11 Shelf Life

270 days from date of packing

12. Storage

Cool dry conditions suitable for food storage

13. Country of Origin of Wheat

Canada

14. Nutritional Information	on		
Typical Values		Per 100g	
Energy	kj	1476	
Energy	Kcal	348	
Fat	g	1.5	
Of which: saturates	g	0.4	
Carbohydrates	g	70.1	
Of which: sugars	g	2.4	
Protein (N x 6.25)	g	14.9	
Salt (Na x 2.5)	g	Trace	
Fibre	g	2.7	

15. Packaging		
Item	Barcode	Material
1 Ekg Dock	5011259008506	Food Grade Paper (12g) Widely Recycled
1.5kg Pack 5011259008506		Plastic closure (glue)
(5 x 1.5kg) Outer	05011259106509	HDPE (28g)
Pallet	-	White Wooden - Exchange

16. Labelling	
BEST BEFORE: DD/MM/YYYY YYDDD HH:MM XXXXX	YYDDD – Packing Date (Year and Julian Day) HH:MM - Packing Time XXXXX – Batch Code

Date Compiled	24/02/21	Specification Reference	MM-12-03-60008D-2
Date Issued	04/07/23	Issued By	C Bunn



17. Allergens

Wheat gluten is present in all products. Other cereal glutens such as rye, barley and spelt may be present. No other allergens are used within the flour mill

The products on the flour mill are produced without the addition of soya in a mill which does not process soya but within a supply chain which handles soya and where a risk may exist. **nabim 2014.**

Egg, Maize, Soya, Fishmeal, Milk powder, Sesame and Peanuts are used or stored on site in a separate factory and warehouse

18. Microbiological

Selected wheats and flours are tested every six months for a range of microbiological species including yeasts and moulds, listeria, bacillus cereus and ecoli. Flour is intended for further thermal processing and therefore should be cooked before eating.

19. Mycotoxins

Selected wheats and flours are tested every 3 months. In addition to this, intakes of wheat into the mill are assessed and a DON test will be carried out if required.

20. Pesticide Residues

Selected wheats and flour are tested every six months

21. Other Contaminant Testing

We participate in nabim/HGCA contaminant monitoring surveys throughout the year which include heavy metal testing.

22. Genetically Modified Policy

We are not aware of any GM wheat that is commercially available.

The ingredients used in the production of our are flours are from non GM sources.

To the best of our knowledge the flours, bran and wheatfeed that we produce are GM free.

23. H	ACCP			
We opera	We operate a HACCP system based on codex alimentarius to ensure food safety.			
Our multi	idisciplinary team are all qualified to Intermediate HACCP level three.			
CCP1	Wheat and Goods Intake – Visual Inspection for Foreign Bodies, Taint and Infestation			
CCP2A Inspection of overtails of control sieves (finest 0.3mm)				
ССРЗВ	Packing line metal detection tests. (Fe – 1.5mm, Non Fe -2.0mm, Stainless Steel – 2.0mm)			

Date Compiled	24/02/21	Specification Reference	MM-12-03-60008D-3
Date Issued	04/07/23	Issued By	C Bunn



24. Produc	t Safety Data	Sheet for Wheat Flour		
Product:		flour is produced by milling d wheat grain.	cleaned wheat grain or endosperm of	
Uses:		Flour is mainly used in the manufacture of bread, confectionery, other food stuffs and for various industrial purposes.		
Legislation:	Act. (EC	Flour is produced so as to comply with the requirements of the Food safety Act. (EC) No 1169/2011, Calcium carbonate purity meets the criteria under (EU) No 231/2012		
Delivery:		Flour is usually supplied either by bulk tanker or in paper bags of various weights of 1.0kg up to 25kg.		
Static Electricity:	electric		n bulk tankers can give rise to static tial for blowlines to be earthed; suitable at the discharge point.	
Manual Handling	be the	All manual handling operations, including those involving flour bags, should be the subject of a risk assessment appropriate to the environment and the physical characteristics of the handlers.		
Storage:		In bulk, flour should be stored at ambient temperature in dry bins. Bagged flour should be stored in cool, dry conditions.		
Health:	ingestic Substan reason practic	In normal use, wheat flour does not present a serious health risk and ingestion has no adverse effects. However, to comply with the Control of Substances Hazardous to Health Regulations and for the general health reasons outlined below, it is necessary to reduce – so far as is reasonably practicable – personal exposure to any dust through enclosure, ventilation and the provision and use of any personal protective equipment.		
	suscep [:] monito Eyes: F running Skin: Fl	 Inhalation: Flour dust may cause asthmatic reactions in a small proportion of susceptible employees. The health of employees exposed to dust should be monitored and any necessary action taken. Eyes: Flour dust may cause discomfort and the eyes should be washed with running water. Medical advice should be sought if the discomfort persists. Skin: Flour can have a drying effect on the skin but is only very rarely, if ever, the cause of dermatitis. 		
Hygiene:	Dust formation should be minimised during handling to prevent inhalation and skin contact. Overalls and dust respirators are recommended when handling loose materials. Spillages should be removed without delay to maintain hygiene standards and to minimise the level of dust in the atmosphere. Vacuum cleaning should be used wherever possible. High standards of personal hygiene should be maintained to avoid the possibility of dermatitis or product contamination.			
Date Compiled	24/02/21	Specification Reference	MM-12-03-60008D-4	

Date Compiled	24/02/21	Specification Reference	MM-12-03-60008D-4
Date Issued	04/07/23	Issued By	C Bunn



Fire / Explosion: Like most organic materials, flour dust is flammable. Although not especially combustible, in certain circumstances flour can form explosive clouds if ignited. The following precautions should be taken to minimise this risk: Adequate extraction facilities should be provided in all areas subject to dust. Care should be taken to prevent the formation of dust clouds in storage and conveying plant. Potential sources of ignition should be avoided. Silos and appropriate equipment, including blowlines, should be earthed to prevent ignition by electrostatic discharge. Adequate extplosion venting should be fitted to silos and other appropriate equipment. Smoking must be prohibited near storage and handling areas. Build-up of dust on beams and ledges should be prevented as this represents a potential dust cloud. Further information on this matter is available in: "The prevention of dust explosions in flour mills and bulk flour containers", nabim, 21 Arlington Street, London. SW1A 1RN. TECHNICAL DATA Particle Size: All particles are smaller than 250 microns; over 50% are smaller than 150 microns. Specific Heat: 0.42 kcal/kg°C Explosive A cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. Layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition. Minimum Ignition A cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types. Kst Values Comprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s⁻¹ depending on particle size distribution and moisture content.<th>-</th><th></th>	-		
to dust.•Care should be taken to prevent the formation of dust clouds in storage and conveying plant.•Potential sources of ignition should be avoided.•Silos and appropriate equipment, including blowlines, should be earthed to prevent ignition by electrostatic discharge.•Adequate explosion venting should be fitted to silos and other appropriate equipment.•Smoking must be prohibited near storage and handling areas.•Build-up of dust on beams and ledges should be prevented as this represents a potential dust cloud.Further information on this matter is available in: "The prevention of dust explosions in flour mills and bulk flour containers", nabim, 21 Arlington Street, London. SW1A 1RN.TECHNICAL DATAParticles are smaller than 250 microns; over 50% are smaller than 150 microns.Specific Heat:0.42 kcal/kg°CExplosive ConcentrationsAbove 50 g m ⁻³ .A cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. Layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition.Minimum IgnitionA cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types.Kst ValuesComprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.	Fire / Explosion:	•	
storage and conveying plant.•Potential sources of ignition should be avoided.•Silos and appropriate equipment, including blowlines, should be earthed to prevent ignition by electrostatic discharge.•Adequate explosion venting should be fitted to silos and other appropriate equipment.•Smoking must be prohibited near storage and handling areas.•Build-up of dust on beams and ledges should be prevented as this represents a potential dust cloud.Further information on this matter is available in: "The prevention of dust explosions in flour mills and bulk flour containers", nabim, 21 Arlington Street, London. SW1A 1RN.TECHNICAL DATAParticle Size:Particle Size:All particles are smaller than 250 microns; over 50% are smaller than 150 microns.Specific Heat:0.42 kcal/kg°CExplosive ConcentrationsAbove 50 g m ⁻³ . A cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. Layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition.Minimum IgnitionA cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types.Kst ValuesComprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.			
 Silos and appropriate equipment, including blowlines, should be earthed to prevent ignition by electrostatic discharge. Adequate explosion venting should be fitted to silos and other appropriate equipment. Smoking must be prohibited near storage and handling areas. Build-up of dust on beams and ledges should be prevented as this represents a potential dust cloud. Further information on this matter is available in: "The prevention of dust explosions in flour mills and bulk flour containers", nabim, 21 Arlington Street, London. SW1A 1RN. TECHNICAL DATA Particle Size: All particles are smaller than 250 microns; over 50% are smaller than 150 microns. Specific Heat: 0.42 kcal/kg°C Explosive A cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. Layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition. Minimum Ignition A cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types. Kst Values Comprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s⁻¹ depending on particle size distribution and moisture content. 		·	
earthed to prevent ignition by electrostatic discharge.Adequate explosion venting should be fitted to silos and other appropriate equipment.Smoking must be prohibited near storage and handling areas.Build-up of dust on beams and ledges should be prevented as this represents a potential dust cloud.Further information on this matter is available in: "The prevention of dust explosions in flour mills and bulk flour containers", nabim, 21 Arlington Street, London. SW1A 1RN.TECHNICAL DATAParticle Size:All particles are smaller than 250 microns; over 50% are smaller than 150 microns.Specific Heat:0.42 kcal/kg°CExplosive ConcentrationsAbove 50 g m ⁻³ . A cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. Layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition.Minimum Ignition Kst ValuesA cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types.Kst ValuesComprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.		 Potential sources of ignition should be avoided. 	
appropriate equipment.•Smoking must be prohibited near storage and handling areas.•Build-up of dust on beams and ledges should be prevented as this represents a potential dust cloud.Further information on this matter is available in: "The prevention of dust explosions in flour mills and bulk flour containers", nabim, 21 Arlington Street, London. SW1A 1RN.TECHNICAL DATAParticle Size:All particles are smaller than 250 microns; over 50% are smaller than 150 microns.Specific Heat:0.42 kcal/kg°CExplosive ConcentrationsAbove 50 g m ⁻³ .A cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. Layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition.Minimum IgnitionA cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types.Kst ValuesComprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.			
Build-up of dust on beams and ledges should be prevented as this represents a potential dust cloud. Further information on this matter is available in: "The prevention of dust explosions in flour mills and bulk flour containers", mabim, 21 Arlington Street, London. SW1A 1RN. TECHNICAL DATA Particle Size: All particles are smaller than 250 microns; over 50% are smaller than 150 microns. Specific Heat: 0.42 kcal/kg°C Explosive Above 50 g m ⁻³ . A cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition. Minimum Ignition A cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types. Kst Values Comprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.			
"The prevention of dust explosions in flour mills and bulk flour containers", nabim, 21 Arlington Street, London. SW1A 1RN.TECHNICAL DATAParticle Size:All particles are smaller than 250 microns; over 50% are smaller than 150 microns.Specific Heat:0.42 kcal/kg°CExplosive ConcentrationsAbove 50 g m ⁻³ .A cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. leading to flames and ignition.Minimum IgnitionA cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types.Kst ValuesComprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.		• Build-up of dust on beams and ledges should be prevented as this	
Particle Size:All particles are smaller than 250 microns; over 50% are smaller than 150 microns.Specific Heat:0.42 kcal/kg°CExplosive ConcentrationsAbove 50 g m-3.A cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. Layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition.Minimum IgnitionA cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types.Kst ValuesComprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.		"The prevention of dust explosions in flour mills and bulk flour containers",	
microns.Specific Heat:0.42 kcal/kg°CExplosive ConcentrationsAbove 50 g m ⁻³ .Ignition TemperatureA cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. Layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition.Minimum Ignition Kst ValuesA cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types.Kst ValuesComprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.	TECHNICAL DATA		
Explosive ConcentrationsAbove 50 g m-3.Ignition TemperatureA cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. Layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition.Minimum IgnitionA cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types.Kst ValuesComprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.	Particle Size:	•	
ConcentrationsA cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. Layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition.Minimum IgnitionA cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types.Kst ValuesComprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.	Specific Heat:	0.42 kcal/kg°C	
Ignition TemperatureA cloud of flour in air can be ignited by surfaces at temperatures of 400 °C. Layers of flour on a hot surface can smoulder at temperatures of 200 °C, leading to flames and ignition.Minimum IgnitionA cloud of flour in air requires an minimum ignition energy of 300MJ. This is the lowest value obtained with a number of flour types.Kst ValuesComprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.	-	Above 50 g m ⁻³ .	
Kst ValuesComprehensive tests on flour indicate a range of Kst between 74 and 137 bar m s ⁻¹ depending on particle size distribution and moisture content.	Ignition	Layers of flour on a hot surface can smoulder at temperatures of 200 $^\circ\mathrm{C}$	
m s ⁻¹ depending on particle size distribution and moisture content.	Minimum Ignition		
Density White Flours: circa 550 kg m ⁻³	Kst Values		
	Density	White Flours: circa 550 kg m ⁻³	

Date Compiled	24/02/21	Specification Reference	MM-12-03-60008D-5
Date Issued	04/07/23	Issued By	C Bunn



25. Relevant Accreditations

British Retail Consortium

Campden Laboratory Accredition Scheme / nabim intake scheme

26. Disclaimer

W & H Marriage and Sons Ltd warrant to supply flour conforming to the above specification. In taking flour conforming to this specification you agree that it is suitable for your requirements.

27.	Specification Authorisation	
		Simon Fortis
	\cap	Technical Manager
		6 th March 2023

Date Compiled	24/02/21	Specification Reference	MM-12-03-60008D-6
Date Issued	04/07/23	Issued By	C Bunn